MATERIAL SAFETY DATA SHEET



PRODUCT NAME: Hemident™

PRODUCT NUMBER: 7812 (1006055) DATE: August 01, 2011

TRADE NAME: Hemident™

GENERAL USE: Presumptive Bloodstain Test

CHEMICAL FAMILY: McPhail's Reagent

PRODUCT DESCRIPTION:

Pale blue-green liquid with Acetic Acid odor.

MANUFACTURER: DATE PREPARED: August 1, 2011
Safariland LLC SUPERSEDES: September 17, 2008

ADDRESS (NUMBER, STREET, P.O. BOX)

TELEPHONE NUMBER FOR INFORMATION / Customer Service

13386 International Parkway 800-347-1200

(CITY, STATE AND ZIP CODE) COUNTRY

Jacksonville, FL. 32218 USA

CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER

ChemTel North Ame

1-800-255-3924North America Toll Free International

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is an irritant to the eyes, skin, and mucous membranes.

POTENTIAL HEALTH EFFECTS

INHALATION:

May cause irritation and damage to the respiratory tract. Symptoms may include coughing and shortness of breath.

SKIN

Irritation, burns, rash, hypersensitivity.

FYFS:

May cause irritation, redness and pain.

INGESTION:

Product should be treated as toxic by ingestion.

CARCINOGENICITY:

NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

CALIFORNIA, Prop.65? NO

SECTION 3 - HAZARDOUS INGREDIENTS					
Hazardous Components	% (by Weight)	CAS#	EINECS#	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Glacial Acetic Acid	30-40	64-19-7	200-580-7	С	R10, R34
Hydrogen Peroxide	1-5	7722-84-1	231-765-0	None	None

Notes:

SECTION 4 - FIRST AID MEASURES

INHALATION:

Remove victim to fresh air. Seek immediate medical assistance. Get medical attention for any breathing difficulty

FYFS:

Flush with water for 15 minutes occasionally lifting the eyelids. Seek medical attention.

SKIN:

Wash with non-abrasive soap and water. Use deluge shower as needed. Seek medical attention for any skin damage.

INGESTION:

Do not induce vomiting. Give plenty of water if victim is conscious and able to swallow. Seek immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Heated product may form toxic and corrosive fumes, but is not expected to be a fire hazard.

EXTINGUISHING MEDIA:

Use media appropriate for surrounding fire. Water may be used to cool product and reduce fumes.

FIRE FIGHTING PROCEDURES:

Emergency responders should wear bunker gear and NIOSH or European EN-149 organic vapor respirators. Avoid exposure to decomposition products (29CFR 1910.156). Proper eye and skin protection should also be used.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Heating may produce toxic and corrosive fumes.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon Oxides, Nitrogen Oxides, Organic Compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

For small spills, suit up in personal protective equipment, use absorbent material to take up material, and place in SEALED container. Flush spill area with plenty of water. For large spills, evacuate area and contact authorities to perform cleanup.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Hemident™

PRODUCT NUMBER: 7812 (1006055) DATE: August 01, 2011

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container tightly closed. Store at room temperature; avoid elevated temperatures. Containers of this material may be hazardous when empty since they retain product residues; observe all warnings and precautions listed for the product.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION								
	NIOSH			ACGIH		OSHA		
HAZARDOUS COMPONENTS	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TLV/TWA ppm	TWA mg/m3	PEL ppm	PEL mg/m3
Glacial Acetic Acid	10	25	15	37	10	25	10	25
Hydrogen Peroxide	1	1.4	75 IDLH		1		1	1.4

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Highly recommended. Use NIOSH or E.U. EN149 standard approved dust respirators for areas where general ventilation is not possible or is insufficient.

PROTECTIVE GLOVES:

Wear gloves while handling product to avoid irritation.

EYE PROTECTION:

Safety glasses or splash goggles are required for handling product.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Eye wash station in the event of eye contact with material. Protective apron in case of splash hazard.

WORK / HYGIENIC PRACTICES:

Employ good, industrial hygiene practices by using adequate ventilation and personal protection, as needed. Do not smoke, eat, or drink while handling product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES			
APPEARANCE AND ODOR	VAPOR PRESSURE		
Pale blue-green liquid with Acetic Acid odor.	NE		
рН	SPECIFIC GRAVITY (WATER = 1)		
NA	NE		
BOILING POINT	SOLUBILITY IN WATER		
NE	Infinite		
FLASH POINT	PERCENT VOLATILE		
NE	ND		
FLAMMABLE LIMITS	VAPOR DENSITY (AIR = 1)		
LEL: NE UEL: NE	NE		
AUTO-IGNITION TEMPERATURE	EVAPORATION RATE (WATER = 1)		
NE	NE		

SECTION 10 - STABILITY AND REACTIVITY

STABILITY STABLE X CONDITIONS TO AVOID: Excessive heat.

INCOMPATIBILITY (MATERIALS TO AVOID):

Oxidizers, Strong Bases.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Oxides of Carbon, Oxides of Nitrogen.

HAZARDOUS POLYMERIZATION:

Will not occur.

CONDITIONS TO AVOID:

None related to polymerization.

SECTION 11 - TOXICOLOGICAL INFORMATION				
Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)	
Glacial Acetic Acid	64-19-7	Oral, Rat: LD50 = 3310 mg/kg	Inhalation, Mouse: LC50=	
	200-580-7	Oral, Rat. LD30 = 3510 llig/kg	5620ppm / 1 hour	
Hydrogen Peroxide	7722-84-1	Oral, rat: LD50 = 376 mg/kg;	Inhalation, rat: LC50 =	
nydrogen Feroxide	231-765-0	Oral, mouse: LD50 = 2000 mg/kg	2000 mg/m3	

SECTION 12 - ECOLOGICAL INFORMATION

Environmental information on product has not been established. Treat product as hazardous. DO NOT RELEASE PRODUCT INTO BODIES OF WATER OR SEWER SYSTEMS.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Dispose of product waste as well as containers in accordance with all local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Hemident™ PRODUCT NUMBER: 7812 (1006055) August 01, 2011 DATE: SECTION 14 - TRANSPORT INFORMATION Acetic Acid, More than 10% but less than 50% by Weight PROPER SHIPPING NAME: DOT HAZARD CLASS / Pack Group: 8 / III Hazard Identification Number (HIN): 80 REFERENCE: **49 CFR** RID/ADR Dangerous Goods Code: 80 UN TDG Class / Pack Group: 8 / III UN / NA IDENTIFICATION NUMBER: **UN 2790** I ABFI · IMDG HAZARD CLASS: Corrosive HAZARD SYMBOLS: IATA HAZARD CLASS / Pack Group: 8/ III - Max Quantities 5L - Passenger (TOTAL) 60L - Cargo Only (TOTAL)

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

Yes

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act):

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act): Yes _ Sections 311 and 312.

Acute Health: Yes Chronic Health: Yes

Fire: NO Sudden Release of Pressure: NO

Reactive: NO

313 REPORTABLE INGREDIENTS: No

CERCLA (USA - Comprehensive Response Compensation and Liability Act):

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: State Right to Know: Acetic acid: MA, NJ, PA; Hydrogen peroxide: MA, NJ, PA.

CPR (Canadian Controlled Products Regulations): Not listed.

CIDL (Canadian Ingredient Disclosure List): Listed.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Components listed on DSL.

EINECS (European Inventory of Existing Commercial Chemical Substances): Referenced.

WGK Water Quality Index: 2		
RISK PHRASES:	SYMBOL(S) REQUIRED FOR EU LABEL	SAFETY PHRASES:
R10 : Flammable. R34 : Causes burns.	C - Corrosive	S1/2: Keep locked up and out of the reach of children. S23: Do not breathe gas/fumes/vapor/spray (appropriate wording to be specified by the manufacturer). S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 16 - OTHER INFORMATION

Legend: NA = Not Applicable,	NE = Not Established, ND = Not Determined, NR = Not Re	ported.	
HMIS HAZARD RATINGS	HEALTH:	1	0 = INSIGNIFICANT
	FLAMMABILITY:	1	1 = SLIGHT
	PHYSICAL HAZARD:	1	2 = MODERATE
	PERSONAL PROTECTIVE EQUIPMENT:		3 = HIGH
		G	4 = EXTREME

REVISION SUMMARY:

Revised to E.U. protocols, supersedes 9/17/08 issue. LB/JTV

MSDS Prepared by:

ChemTel Inc.

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

1305 North Florida Avenue



Yes-RQ for Acetic Acid=5000 lbs.

Not listed.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if easonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described n Section 1